



**“Prices are subject to daily fluctuations in foreign exchange”**

**A. Electric Bicycles, Scooters and Accessories; (For Mobility, Fun and Fitness)**







S/N	MODEL	FEATURES	PRICE (₦)
1.	 <p><b>RS-A02</b></p>	<b>Frame:</b> 20" aluminum alloy 6061 large tube 099 four-link suspension folding frame <b>Front fork:</b> double shoulder aluminum alloy motorcycle suspension fork with lock <b>Battery:</b> 48V17AH 2900 cell lithium battery(DMC 18650) <b>Motor:</b> 48V1200W high speed brushless high power fat tire motor <b>Derailleur:</b> TZ500GSD Shimano 7S <b>Display:</b> YL-90V-H Middle colorful LCD display + USB charger <b>Driving mode:</b> T001 Electrical/5 speed PAS <b>Brakes:</b> HD-E500 dual pump hydraulic disc brake <b>Saddle:</b> PU widened vacuum comfortable saddle <b>Tires:</b> 20*4.0 inch KENDA wide fat tires. reflective rims <b>Rim:</b> Magnesium Alloy rim (12 lines) <b>Mudguard:</b> PVC all-inclusive adjustable mudguard <b>Rear carrier:</b> Aluminum alloy ED thickened rear carrier <b>Light set:</b> front LED lights, rear LED brake lights <b>Remarks:</b> Vehicle quick release waterproof wiring	<b>1,550,000</b>
		<b>Combo +Helmet+Lock+ Phone holder</b>	<b>1,580,000</b>
2	 <p><b>SY26</b></p>	<b>Frame</b> 26" high-carbon steel mountain frame, <b>Fronk fork:</b> Suspension fork <b>Brake:</b> mechanical Disk Brake <b>Handle Bar tube :</b> aluminum alloy <b>Derailleur</b> SHIMANO 7Speed <b>Battery:</b> 36V 12AH Lithium-ion Battery <b>Motor:</b> 480watts; High Speed Brushless <b>Driving Mode:</b> Electrical & PAS <b>Meter:</b> LCD Middle Meter <b>Tire:</b> 26"1.95" Chaoyang tires <b>RIM:</b> Spoke rim <b>Mudpate:</b> PVC	<b>850,000</b>
		<b>Combo +Helmet+Lock</b>	<b>880,000</b>
3	 <p><b>SM-C02</b></p>	<b>Frame:</b> 14"high-carbon steel frame <b>Front fork:</b> straight leg fork <b>Battery:</b> 36V13AH lithium battery (Internal battery) <b>Motor:</b> 36V500W High speed brushless gear motor <b>Meter:</b> handle LCD meter +Key <b>Brake:</b> mechanical disc brake <b>Tires:</b> 14"*1.95" tires <b>Rim:</b> Aluminum alloy conjoined rim (7 lines) <b>Mudplate:</b>	<b>630,000</b>
		<b>Combo +Helmet+Lock</b>	<b>660,000</b>

“Prices are subject to daily fluctuations in foreign exchange”

4.	 <p>GM Pro-2 Electric Bicycle</p>	<p>Frame: 20" <b>Steel Electrophoresis</b> Motorcycle frame          Front rk: 20" Two shoulders suspension fork with lock          Brake: 180 Hydraulic disc brake          Shock absorber: BCA09 1000 pounds Adjustable aluminum alloy          Deraillieur: M315 SHIMANO 7Speed          Battery: 48V/20Ah 18650, 2600DMC lithium-ion.          Motor: <b>1000W</b> high speed high power fat tire motor          Driving Mode: Electrical &amp; PAS          Meter: YL81F LCD Middle meter with USB          Speed: 35km/h (Europe), 45km/h (USA).          Tires: CTS 20"*4.0" <b>Puncture-proof</b> fat tires          Rim: <b>alloy wheel</b>          Mudplate: PVC Mudplate (front and rear)</p>	1,570,00
			<p>Combo +Helmet+Lock+ Phone holder  1,600,000</p>
5.		GM-Bikes ABS Multipurpose Sports Helmet	30,000
6.		Phone holder	5,500
7..		Bike Lock (with 2keys)	5,000

**“Prices are subject to daily fluctuations in foreign exchange”**

**B. Sun king Solar Lamps**

S/N	MODEL FEATURES		PRICE (₦)
<b>LAMPS</b>			
1		<b>PICO PLUS</b> 50 Lumens, 5x brighter than kerosene lamps, 72hrs run time. 350mW integrated Solar Panel, 425 mAh Battery Capacity ,5yrs Battery Life, 2yrs Warranty	<b>9,000</b>
2		<b>PRO 200</b> 200 Lumens, 20x brighter than kerosene lamps, 72hrs run time. 2.35W Solar Panel, USB Mobile Phone Charging Port, 2200mAh Battery Capacity ,5yrs Battery Life, 2yrs Warranty	<b>23,600</b>
3		<b>PRO 400</b> 400 Lumens, 40x brighter than kerosene lamps, 100hrs run time. 5.5 W Solar Panel, USB Mobile Phone Charging Port ,4400mAh Battery Capacity,5yrs Battery Life, 2yrs Warranty	<b>35,000</b>
4		<b>BOOM</b> 160 Lumens, 16x brighter than kerosene lamps, 36hrs run time. 2.7 W Solar Panel, USB Mobile Phone Charging Port ,3000mAh Battery Capacity,5yrs Battery Life, 2yrs Warranty	<b>42,800</b>
5.		<b>PORTABLE SOLAR TUBE CLASSIC (with Mobile charging)</b> 400 Lumens, 5.5watt 6v Poly solar panel, 40x brighter than kerosene lamps, 48hrs on low mode, 10hrs on Normal Mode, 5hrs on Turbo Mode,5v 1A USB Mobile Charging,5100mAh Battery Capacity,2yrs Warranty.	<b>41,000</b>
6.		<b>SOLAR TUBE LIGHT 200 Lumens</b>	<b>14,800</b>




**“Prices are subject to daily fluctuations in foreign exchange”**

**C. SUNKING HOME SYSTEMS.**

S/N	MODEL FEATURES	PRICE (₦)
1.	 <p><b>HOME Plus</b></p> <p>1 Tube Lights (240 Lumens), 2 hanging lights (120 Lumens), 48x brighter than kerosene lamps, 43hrs runtime on low power mode, 7 Watts, 9v Solar Panel with 8-metre rodent-resistant cable, 2 x 12 V DC output ports for lighting (550 mA max. total) 1 x USB-A phone charging port (5 V, 1.0 A) ,3.2 V, 19.2 Wh lithium ferro-phosphate (LFP) battery Estimated 10 year lifespan (2,500 cycles),2years Warranty</p>	<b>65,000</b>
2.	 <p><b>HOME Plus Pro</b></p> <p>4 Tube Lights (240 Lumens), 90x brighter than kerosene lamps, 30hrs runtime, ,2 USB Mobile Phone Chargin, 2 x 12 V DC output ports for lighting (550 mA max. total) 1 x USB-A phone charging port (5 V, 1.8 A)13 Watts, ,3.2 V, 38.4 Wh lithium ferro-phosphate (LFP) batteryEstimated 10 year lifespan (2,500 cycles) 2years Warranty</p>	<b>85,000</b>
3.	 <p>4 Tube Lights (200x4 Lumens), 1 motion sensing light (100lumens), 30hrs runtime, 50W/16v Solar Panel,1 USB Mobile Phone Charging Port, 141. Lithium-NMC Battery ,8hrs Runtime (Tv +light), 2yrs Warranty</p>	<b>165,000</b>

**“Prices are subject to daily fluctuations in foreign exchange”**

**D. SUNKING FANS/DC Television**

S/N	MODEL FEATURES	PRICE (₦)
<p>1.</p> 	<p><b>SUNKING DC Television</b> HD LED TV, BUILT-IN DIGITAL TV DECODER. SUPER HIGH EFFICIENCY, FULL VIEW ANGLE, <b>1year warranty.</b></p>	<p><b>32” TV = 260,000</b></p>
<p>2.</p> 	<p><b>SOLAR TABLE FAN</b> 1300 RPM On Turbo Speed, 3 Power Modes , Blows up to 6.2 Metres, Heavy Duty Batteries , Brushless DC Motor, 20 Watts Power, <b>1year warranty.</b></p>	<p><b>90,000</b></p>
<p>3.</p> 	<p><b>PEDESTAL FAN</b> 24 Hours Wind on Low Mode, 3 Power Modes, 5 m/s Air Speed, Long life Span, Brushless DC Motor, <b>10 Watts Power, 1year warranty.</b></p>	<p><b>58,000</b></p>

**“Prices are subject to daily fluctuations in foreign exchange”**

**E. LEAD ACID TUBULAR BATTERIES**

<b>S/N</b>	<b>BATTERY TYPE</b>	<b>EXPECTED LIFESPAN</b>	<b>PRICE (₦)</b>
1	<b>12-200AH Tandhan NXT DRY CELL (12 Months Warranty)</b>	2-4years expected lifespan (Maintenance free)	<b>385,000</b>
2.	<b>12v-220AH ADWIN/ENERGOS/OZORO (24 Months Warranty)</b>	3-5years+ Lifespan, (Once in <b>6months+</b> <b>maintenance required</b> )	<b>265,000</b>
3.	12v-220AH Tandhan ROYAL <b>(24 Months Warranty)</b>	3-5years+ Lifespan, (Once in <b>6months+</b> <b>maintenance required</b> )	<b>265,000</b>
4.	12v-230AH Tandhan ROBUST <b>(24 Months Warranty)</b>	3-6years+ Lifespan, (Once in <b>7months+</b> <b>maintenance required</b> )	<b>275,000</b>





**“Prices are subject to daily fluctuations in foreign exchange”**

**F. LITHIUM BATTERIES (DEYE - 5yr/10yrs Warranty-Digital Display)**

1.	<b>5.12kWh (DEYE) (SE-G5.1 Pro-B) (10years Warranty) (Wall Mounted, Floor mounted, Stack Mounted)</b>	<b>5.1kWh: 51.2V 100AH Lithium Battery.1C ,Supports up to 64 in parallel) 6000cycles@90% DOD 15yrs+ expected lifespan. IP21: Indoor Use</b>	<b>1,135,000</b> 
2.	<b>10.24kWh (DEYE) (SE-G10.2) (5years Warranty) (Stackable)</b>	<b>10.24kWh: 51.2V 200AH Lithium Battery.0.5C, Supports up to 64 in parallel) ≥ 6000cycles@ 80% DOD 15yrs+ expected lifespan. IP21: Indoor Use (very compact for easy scalability)</b>	<b>1,900,000</b> 
3.	<b>16kWh (DEYE) (SE-F16-C ) (5years Warranty) (Standing Model-Digital Display)</b>	<b>16kWh: 51.2V 314 AH Lithium Battery. (supports up to 32units in parallel) 6000cycles@90% DOD, 15yrs+ expected lifespan</b>	<b>2,700,000</b> 
	<b>DEYE HIGH VOLTAGE LITHIUM AND ACCESSORIES</b>	<b>ADVANCED COMMERCIAL SOLUTION FOR High Voltage Inverters</b>	
4.	<b>DEYE BOS PACK 7.6kWh 10years warranty</b>	<b>7.68kWh, 38.4V, 200Ah. Charge/Discharge Amps :100A Minimum</b>	<b>1,785,000</b>
5.	<b>DEYE BOS A-Control BOX</b>	<b>CONTROL BOX HV-BOS-A-PDU-2 Suitable for high-voltage clusters, supporting up to 1000V systems and 160A Protection: Integrated BMS protects against over-discharge, overload, over-voltage, and over-temperature</b>	<b>1,540,000</b>
6.	<b>RACK-BOS-A-14</b>	<b>RACK-BOS-A-R14- 14 LAYER</b>	<b>504,000</b>
7.	<b>RACK-BOS-A-11</b>	<b>RACK-BOS-A-R11- 11 LAYER</b>	<b>415,000</b>



**“Prices are subject to daily fluctuations in foreign exchange”**

**G. LITHIUM BATTERIES (SRNE - 10year Warranty-Digital Display, Cycle Monitor, inbuilt mobile app connectivity)**

1.	<b>2.56kWh (SRNE) (SR-EOSO2B-12) (5years Warranty) WALL MOUNT- LED DISPLAY</b>	<b>2.56kWh: 12.8V 200AH Lithium Supports up to 4 batteries in parallel, 6000cycles @ 80% DOD 10years+ Expected Lifespan LED Display</b>	
2.	<b>5kWh (SRNE) (EOS05B) (10years Warranty) (WALL MOUNT-Digital Display)</b>	<b>5.12kWh: 51.2V 100AH Lithium Battery. (supports up to 16 in parallel) 6000cycles@80% DOD 15yrs+ expected lifespan With cycle monitor, mobile app and remote monitoring</b>	<b>1,325,000</b> 
3.	<b>10kWh (SRNE) (EOS10B) (10years Warranty) (WALL MOUNT-Digital Display)</b>	<b>10.24kWh: 51.2V 200AH Lithium Battery. (supports up to 16 in parallel) 6000cycles@80% DOD, 15yrs+ expected lifespan With cycle monitor, mobile app and remote monitoring</b>	<b>2,750,000</b> 
4.	<b>16kWh (SRNE) (EOS15B) (10years Warranty) (Standing Model-Digital Display)</b>	<b>16kWh: 51.2V 314 AH Lithium Battery. (supports up to 16 in parallel) 8000cycles@80% DOD, 15yrs+ expected lifespan With cycle monitor, mobile app and remote monitoring</b>	<b>3,360,000</b> 






**“Prices are subject to daily fluctuations in foreign exchange”**

**H. LITHIUM BATTERIES -LV Topsun (10years Warranty)**

S/N	MODEL	SPECIFICATION	PRICE
1.	<p><b>16kWh-51.2V LVTS-512314-G4 Digital Touch Display (10years Warranty)</b></p> 	<p><b>51.2V-314Ah</b>  <b>Performance Data</b>            Norminal Voltage : 51.2 Vdc            Nominal Capacity: 314AH            Battery Capacity : 16.07kWh            Working Voltage : 45.6 - 56.16V            Charge Current: 150A(7680 W)            Discharge Current : 200A (10240W)  <b>Communication:</b>            Display:SOC Status Indicator, LCD            Communication: RS232, RS485, CAN  <b>Product Feature: Automatic Sensing, Fire            extinguishing device / Bluetooth/WiFi</b>  <b>Weight : 120KG</b>  <b>IP rating: IP65 (outdoor and indoor)</b>  <b>Cycle Life : 8000cycles @ 90% DOD</b>  <b>Scalability: Maximum 63 batteries</b>  <b>Experience the power of G4</b>  <b>15years+ Design Life</b></p>	2,700,000
2.	<p><b>16kWh-51.2V LVTS-512314-G3 Digital Touch Display (5years Warranty)</b></p> 	<p><b>51.2V-314Ah</b>  <b>Performance Data</b>            Norminal Voltage : 51.2 Vdc            Nominal Capacity: 314AH            Battery Capacity : 16.07kWh            Working Voltage : 45.6 - 56.16V            Charge Current: 150A(7680 W)            Discharge Current : 200A (10240W)  <b>Communication:</b>            Display:SOC Status Indicator, LCD            Communication: RS232, RS485, CAN  <b>Product Feature: Automatic Sensing, Fire            extinguishing device / Bluetooth/WiFi</b>  <b>Weight : 119KG</b>  <b>IP rating: IP20 (indoor only)</b>  <b>Cycle Life : 8000cycles @ 90% DOD</b>  <b>Scalability: Maximum 63 batteries</b>  <b>15years+ Design Life</b></p>	2,200,000






**“Prices are subject to daily fluctuations in foreign exchange”**

**I. LITHIUM BATTERIES (ITEL -5year Warranty)**

S/N	MODEL	SPECIFICATION	PRICE
1.	<b>2.56kWh-24v</b> <b>(IPW-25100)</b> 	<b>25.6v-100Ah</b> <b>Operating Range: 20v-28.8v</b> <b>RS485/RS232/CAN Communication</b> 6000 cycles @ 80% DOD, up to 4units in parallel- LED Display- Wall mount <b>10years+ Design Life</b>	<b>600,000</b>
2.	<b>5kWh-48v</b> <b>(IPW-51100)</b> 	<b>51.2v-100Ah</b> <b>Operating Range: 40v-57.6v</b> 6000 cycles @ 80% DOD, up to 15units in parallel- LED Display- Wall mount <b>10years+ Design Life</b>	<b>990,000</b>
3.	<b>5kWh-24v</b> <b>(IPW-25200)</b> 	<b>25.6v-200Ah</b> <b>Operating Range: 40v-57.6v</b> 6000 cycles @ 80% DOD, up to 15units in parallel- LED Display- Wall mount <b>10years+ Design Life</b>	<b>1,030,000</b>
4.	<b>10kWh-48V</b> <b>(IPL-51200)</b> 	<b>10kWh -48V</b> <b>51.2-200Ah</b> 6000 cycles @ 80% DOD, up to 15units in parallel- LED Display, Wall mount <b>10years+ Design Life</b>	<b>1,890,000</b>
5.	<b>16.07kWh-48V</b> <b>(IPL-51314H)</b> 	<b>16.07kWh - 48V</b> <b>51.2-314Ah (IP21-indoor use)</b> 6000 cycles @ 80% DOD, up to 15units in parallel- LED Display – Standing Model <b>10years+ Design Life</b>	<b>2,350,000</b>

**“Prices are subject to daily fluctuations in foreign exchange”**

**J. Stackable Lithium Batteries (for large battery banks)**

S/N	MODEL	SPECIFICATION	PRICE
1.	<b>ITEL 5kWh-48V (IPL-51100)</b> 	<b>51.2v-100Ah</b> <b>Operating Range: 40v-58.4v</b> 6000 cycles @ 80% DOD, up to 15units in parallel- IP21 <b>10years+ Design Life</b> <b>5years Warranty</b>	-----
2.	<b>GROWATT 5kWh-48v (HOPE 5.5L-A1)</b> 	<b>51.2v-100Ah</b> <b>Operating Range: 40v-58.4v</b> 6000 cycles @ 93% DOD, up to 12units in parallel- IP20 <b>10years+ Design Life</b> <b>5years Warranty</b>	-----
3.	<b>SRNE 5kWh-48V (EOC05B)</b> 	<b>51.2v-100Ah</b> <b>Operating Range: 44.8v-57.6v</b> 6000 cycles @ 80% DOD, up to 16units in parallel- LED Display- Wall mount <b>15years+ Design Life</b> <b>5years Warranty</b>	-----
4.	<b>DEYE 5kWh -48V (BOS-SE-G5.1 LV)</b> 	<b>51.2-100Ah</b> <b>Operating Range: 44.8v-57.6v</b> 6000 cycles @ 80% DOD, up to 64units in parallel- LED Display- Wall mount <b>10years+ Design Life</b> <b>5years Warranty</b>	-----
5.	<b>PYLONTECH 5kWh-48V (UF 5000)</b> 	<b>51.2-100Ah</b> <b>Operating Range: 44.8v-57.6v</b> 6000 cycles @ 95% DOD, up to 20units in parallel <b>15years+ Design Life</b> <b>5years Warranty</b>	<b>1,180,000</b>

**“Prices are subject to daily fluctuations in foreign exchange”**

**K. WALL-MOUNT, HIGH FREQUENCY HYBRID INVERTERS**

<b>S/N</b>	<b>GROWATT (18Months-60Months Warranty)</b>	<b>PRICE(N)</b>
<b>1.</b>	<b>Growatt 5kW-48Vdc (SPF 5000 ES)</b> <b>6000W</b> Maximum PV POWER, Max PV input current 22A, <b>100A Solar Charge Current</b> , 450VDC Maximum PV Array Open Circuit, 120VDC - 430VDC MPPT Operating range, 80A Maximum AC charge current. <i>WIFI-F dongle inclusive for remote monitoring. Parallel compatibility of up to 6units to get 30kW.</i> <b>(IP20-Indoor use only -18months warranty)</b>	-----
<b>2.</b>	<b>Growatt 6kW-48Vdc (SPF 6000 ES PLUS)</b> <b>8000W</b> Maximum PV Power (dual MPPT Input of 4000Watts Maximum Each), Max PV input current 16A , <b>100A Solar Charge Current</b> , <b>500VDC Maximum PV</b> Array Open Circuit, <b>120VDC - 450VDC</b> MPPT Operating range, 80A Maximum AC charge current. <i>Wifi-F dongle inclusive for remote monitoring. Parallel compatibility of up to 6units to get 36kW.</i> <b>(IP20-Indoor use only -18months warranty),</b>	<b>550,000</b>
<b>3.</b>	<b>Growatt 3.6kW -48v (SPH 3600TL-BL-UP)</b> <b>7500Wp</b> Maximum PV Power Dual MPPT, DC/AC Ratio 1.5, Max <b>PV input current 13.5A(Isc 16.9A)</b> ., Smart load Management via dry contact, UPS function (transfer time less than 10ms), Grid side parallel function, <b>550V Maximum PV</b> Array Open Circuit, <b>120VDC - 550V/370V</b> MPPT Operating range, <b>75A</b> Maximum AC charge current., Shine wifi-X inclusive for remote monitoring, <i>Parallel compatibility of up to 6units</i> <b>Inbuilt Protection : dc switch, dc reverse polarity protection, AC/DC surge protection typeII, battery reverse protection, AC short-circuit protection, Ground fault monitoring.</b> <b>(IP65-Indoor and outdoor use only -60months warranty)</b>	-----
<b>4.</b>	<b>Growatt 5.0kW -48v (SPH 5000TL-BL-UP)</b> <b>9500Wp</b> Maximum PV Power Dual MPPT, DC/AC Ratio 1.5, Max <b>PV input current 13.5A(Isc 16.9A)</b> , Smart load Management via dry contact, UPS function (transfer time less than 10ms), Grid side parallel function, <b>500VDC Maximum PV</b> Array Open Circuit, <b>120VDC - 550VDC/370V</b> MPPT Operating range, 22A Maximum Output current, 85Amps maximum charge and discharge dc current, Shine wifi-X inclusive for remote monitoring, <i>Parallel compatibility of up to 6units.</i> <i>Inbuilt Protection : dc switch, dc reverse polarity protection, AC/DC surge protection typeII, battery reverse protection, AC short-circuit protection, Ground fault monitoring,</i> <b>(IP65-Indoor and outdoor use only -60months warranty).</b>	-----

**“Prices are subject to daily fluctuations in foreign exchange”**

	<b>ITEL (24Months Warranty-36months/60months)</b>	<b>PRICE (N)</b>
1.	<b>ITEL 3.0kW-24V</b> <b>3000Watts Maximum PV Power. Max PV input current 18A, 100A MAX Solar Charge Current, 500VDC Maximum PV Array Open Circuit, 45VDC - 450VDC MPPT Operating range, 20A Maximum AC charge current, (No Parallel compatibility) (IP54-Indoor use only -36months warranty),</b>	<b>325,000</b>
2.	<b>ITEL 4.0 kW-24V</b> <b>6000Watts Maximum PV Power. Max PV input current 15A, 120A MAX Solar Charge Current, 500VDC Maximum PV Array Open Circuit, 85VDC - 450VDC MPPT Operating range, 28A Maximum AC charge current, (No Parallel compatibility), dual output, inbuilt wifi (IP 54 Indoor and outdoor use -36months warranty),</b>	<b>415,000</b>
3	<b>ITEL 6.0 kW -48v</b> <b>8000Watts Maximum PV Power. Max PV input current 27A, Isc 32A, 100A MAX Solar Charge Current, 500VDC Maximum PV Array Open Circuit, 85VDC - 450VDC MPPT Operating range, 50A Maximum AC charge current, . WIFI-F dongle inclusive for remote monitoring. Parallel compatibility of up to 12units. (IP 54 Indoor use and outdoor use -36months warranty)</b>	<b>580,000</b>
4	<b>ITEL 8.0 kW -48v</b> <b>16,000Watts Maximum PV Power. Max PV input current 30V+15V, Isc 34A+19A, 500VDC Maximum PV Array Open Circuit, 85VDC - 450VDC MPPT Operating range, 36.4A Maximum AC charge current, 160A Maximum MPPT Charge current. WIFI-F dongle inclusive for remote monitoring. Parallel compatibility: single phase 9, Three phase 12units. (IP 54 Indoor use and outdoor use -36months warranty)</b>	<b>780,000</b>
5	<b>12kW-48v (using ITEL 12.0 kW -48v)</b> <b>16,000Watts Maximum PV Power. Max PV input current 27A+27V, Isc 32A+32A, 500VDC Maximum PV Array Open Circuit, 85VDC - 450VDC MPPT Operating range, 90A Maximum AC charge current, 210A Maximum MPPT Charge current. WIFI-F dongle inclusive for remote monitoring. Parallel compatibility: single phase 6, Three phase 12units. 12units. (IP 54 Indoor use and outdoor use -36months warranty)</b>	<b>1,250,000</b>

**“Prices are subject to daily fluctuations in foreign exchange”**

	<b>SRNE (24-60Months Warranty)</b>	<b>PRICE (N)</b>
1.	<b>SRNE 1.5kW- 12V (HF1215S60-108)</b> <b>1000Watts Maximum PV Power.</b> Max PV input current 28.5A, <b>60A Solar Charge Current,108VDC</b> Maximum PV Array Open Circuit, <b>15VDC - 90VDC MPPT Operating range</b> , 60A Maximum AC charge current. <b>(IP20 24months Warranty)</b>	<b>295,000.00</b>
2.	<b>SRNE 3.3kW-24 (HF2430S80-H)</b> <b>4000Watts Maximum PV Power.</b> Max PV input current 50A, <b>80A Solar Charge Current, 500VDC</b> Maximum PV Array Open Circuit, <b>120VDC - 450VDC MPPT Operating range</b> , 40A Maximum AC charge current. <b>(IP20-Indoor use 24months Warranty)</b>	-----
3.	<b>SRNE 5.0kW -48V(AFP4850S100-H)</b> <b>7500Watts Maximum PV Power.MPPT</b> Max PV input current 22A,10,000Watts Surge Power, <b>100A Solar Charge Current,</b> 500VDC Maximum PV Array Open Circuit, 120VDC - 450VDC MPPT Operating range, 60A Maximum AC charge current. 4HP Capacity, <b>Upto 6units in Parallel</b> <b>(IP20-Indoor use 24months warranty)</b>	<b>535,000.00</b>
5.	<b>SRNE 6.0kW-48V (AEP4860S135-H)</b> <b>12000Watts Maximum PV Power. Dual MPPT Input, 6000Wp Per MPPT</b> Max PV input current (22A+22A),12,000Watts Surge Power for 10s, <b>135A Max PV Charge current,</b> 500VDC Maximum PV Array Open Circuit, 65VDC - 450VDC MPPT Operating range. 5HP Capacity, <b>Upto 6units in Parrallel</b> <b>(IP65 Indoor and outdoor use – 60 months warranty)</b>	<b>730,000</b>
6.	<b>SRNE 10kW-48Vdc(ASP48100S200-H)</b> <b>11000W</b> Maximum PV Power ( <b>dual MPPT</b> Input of <b>5,500Watts</b> Maximum Each, <b>11,000Wp</b> total), Max PV input current 22A , <b>200A Solar Charge Current,</b> 500VDC Maximum PV Array Open Circuit, <b>125VDC - 450VDC</b> MPPT Operating range, 120A Maximum AC charge current. <b>Upto 6units in Parrallel</b> <b>(IP20 Indoor use-24months warranty)</b>	<b>1,330,000.00</b>

**“Prices are subject to daily fluctuations in foreign exchange”**

7.	<b>SRNE 12kw (ASP48120S200-H)</b> Battery Voltage: 40-60, compatible with Lithium and Lead Acid, Max AC Charging amps 120amps, Max PV Input Power: 13,200watts (6600wattsx2), Max PV Input Voltage : 500V Max.Operating PV Input Current: 22A +22A Max.Input,Short.Circuit.Current: 37A+37A MPPT Voltage Range: 120-450 AC Peak Power : 24,000 Watts(for 3s Max),Number of Tracker 2(1 string per tracker). 200A MPPT Dual MPPT <b>(IP21 Indoor use-24 months warranty)</b>	<b>1,440,000</b>
8.	<b>SRNE 12kw (HESP48120S200-H)</b> Battery Voltage: 40-60, compatible with Lithium and Lead Acid, Max AC Charging amps 120amps, Max PV Input Power: 13,200watts (6600wattsx2), Max PV Input Voltage : 500V Max.Operating PV Input Current: 22A +22A Max.Input,Short.Circuit.Current: 37A+37A MPPT Voltage Range: 120-450 AC Peak Power : 24,000 Watts(for 3s Max),Number of Tracker 2(1 string per tracker). 200A MPPT Dual MPPT <b>(IP65 Indoor and outdoor use-60months warranty)</b>	<b>2,550,000</b>
<b>DEYE INVERTERS</b>		
1	<b>Deye 3.6kW-48V (OGO1LP1)</b> Battery Type: Lithium/LeadAcid(40-60V) Max. DC. Charging Current(A) : 90A Maximum DC. Discharging Current(A): 90A Charging Strategy for Li-ion Battery (Self Adaption to BMS) Max. PV Access Power 7200W, Max. PV Input Power 5760W Max. PV. Input Voltage 500V,Start-up Voltage: 125V MPPT Voltage Range (V) 150-425 Output: 220/230-Single Phase Max. Operating PV Input Current: 18A +18A Max Input Short-Circuit: 27A + 27A No. of MPP Trackers: 2(1+1) Peak Power: 2times of rated power, 10s Parallel Function: Up to 16units (with wifi module attached) <b>IP 65: 5years Warranty</b>	<b>520,000</b>

**“Prices are subject to daily fluctuations in foreign exchange”**

2	<p><b>Deye 6kW-48V (OGO1LP1)</b>            Battery Type: Lithium/LeadAcid(40-60V)            Max. DC. Charging Current(A) :135A            Maximum DC. Discharging Current(A): 135A            Charging Strategy for Li-ion Battery (Self Adaption to BMS)            Max. PV Access Power 12,000W,Max. PV Input Power 9600W            Max. PV. Input Voltage 500V,Start-up Voltage: 125V            MPPT Voltage Range (V) 150-425            Output: 220/230-Single Phase            Max. Operating PV Input Current: 18A +18A            Max Input Short-Circuit: 27A + 27A            No. of MPP Trackers: 2(1+1)            Peak Power: 2times of rated power, 10s            Parallel Function: Up to 16units (with wifi module attached)            IP 65: 5years Warranty</p>	600,000
3	<p><b>Deye 8kW-48V (SUN-8K-SG05LP1-EU)</b>            Battery Type: Lithium/Lead Acid(40-60V)            Max. DC Charging Current(A) :190A            Maximum DC Discharging Current(A): 190A            Charging Strategy for Li-ion Battery (Self Adaption to BMS)            Max. PV Access Power 16,000W, Max. PV Input Power 12,800W            Max. PV. Input Voltage 800V , Start-up Voltage : 160V            MPPT Voltage Range (V) 200-650            Output: 220/230-Single Phase            Max. Operating PV Input Current: 32A +32A,            Max Input Short-Circuit: 48A + 48A            No. of MPP Trackers: 2(2+2)            Peak Power: 2times of rated power, 10s            Parallel Function: Up to 16units (with wifi module attached)            IP 65: 5years Warranty</p>	1,680,000
3	<p><b>Deye 8kW-48V (SUN-8K-SG04LP3-EU)</b>            Battery Type: Lithium/Lead Acid(40-60V)            Max. DC Charging Current(A): 190A            Maximum Discharging Current(A): 190A            Charging Strategy for Li-ion Battery (Self Adaption to BMS)            Max. PV Access Power:16,000W            Max. PV Input Power: 12,000W            Max. PV. Input Voltage: 800V            Start-up Voltage: 160V            MPPT Voltage Range (V) 200-650            Output: 220/380V/230V/400V-Three Phase            Max. Operating PV Input Current: 13A +13A            Max Input Short-Circuit: 17A + 17A            No. of MPP Trackers: 2(1+1)            Peak Power: 2times of rated power, 10s            Parallel Function: Up to 16units (with wifi module attached)            IP 65: 5years Warranty</p>	2,000,000
4.	<p><b>Deye 12kW-48V (SUN-12K-SG02LP1-EU)</b>            Battery Type: Lithium/Lead Acid: (40-60V)            Max. DC Charging Current(A) :240A</p>	2,600,000

**“Prices are subject to daily fluctuations in foreign exchange”**

	<p><b>Maximum DC Discharging Current(A): 240A</b>  <b>Charging Strategy for Li-ion Battery (Self Adaption to BMS)</b>  <b>Max. PV Access Power: 24,000W</b>  <b>Max. PV Input Power: 18,000W</b>  <b>Max. PV. Input Voltage :800V</b>  <b>Start-up Voltage : 160V</b>  <b>MPPT Voltage Range (V) 200-625</b>  <b>Output: 220/230V-Single Phase</b>  <b>Max. Operating PV Input Current: 26A +13A</b>  <b>Max Input Short-Circuit: 34A + 17A</b>  <b>No. of MPP Trackers: 2(2+1)</b>  <b>Peak Power: 2times of rated power, 10s</b>  <b>IP 65: 5years Warranty</b></p>	
<b>5.</b>	<p><b>Deye 12kW-48V (SUN-12K-SG04LP3-EU)</b>  <b>Battery Type: Lithium/Lead Acid: (40-60V)</b>  <b>Max. DC Charging Current(A) :240A</b>  <b>Maximum DC Discharging Current(A): 240A</b>  <b>Charging Strategy for Li-ion Battery (Self Adaption to BMS)</b>  <b>Max. PV Access Power: 24,000W</b>  <b>Max. PV Input Power: 18,000W</b>  <b>Max. PV. Input Voltage :800V</b>  <b>Start-up Voltage : 160V</b>  <b>MPPT Voltage Range (V) 200-625</b>  <b>Output: 220/380V, 230V/400V-Three Phase</b>  <b>Max. Operating PV Input Current: 26A +13A</b>  <b>Max Input Short-Circuit: 34A + 17A</b>  <b>No. of MPP Trackers: 2(2+1)</b>  <b>Peak Power: 2times of rated power, 10s</b>  <b>IP 65: 5years Warranty</b></p>	<b>2,600,000</b>
<b>6.</b>	<p><b>DEYE 16K-48V (SUN-16K-SG01P1-EU)</b>  <b>Battery Type: Lithium/Lead Acid: (40-60V)</b>  <b>Max. DC Charging Current(A) :240A</b>  <b>Maximum DC Discharging Current(A): 240A</b>  <b>Charging Strategy for Li-ion Battery (Self Adaption to BMS)</b>  <b>Max. PV Access Power: 32,000W</b>  <b>Max. PV Input Power: 25,600W</b>  <b>Max. PV. Input Voltage :800V</b>  <b>Start-up Voltage : 160V</b>  <b>MPPT Voltage Range (V) 160-650</b>  <b>Output: 220V/230V/-Single Phase</b>  <b>Max. Operating PV Input Current: 36A +20A</b>  <b>Max Input Short-Circuit: 54A + 30A</b>  <b>No. of MPP Trackers: 2(2+1)</b>  <b>Peak Power: 2times of rated power, 10s</b>  <b>IP 65: 5years Warranty</b></p>	<b>3,500,000</b>

**“Prices are subject to daily fluctuations in foreign exchange”**

<p><b>7.</b></p>	<p><b>DEYE 16K-48V (SUN-16K-SG05LP3-EU)</b>            Battery Type: Lithium/Lead Acid: (40-60V)            Max. DC Charging Current(A) :240A            Maximum DC Discharging Current(A): 240A            Charging Strategy for Li-ion Battery (Self Adaption to BMS)            Max. PV Access Power: 32,000W            Max. PV Input Power: 25,600W            Max. PV. Input Voltage :800V            Start-up Voltage : 160V            MPPT Voltage Range (V) 160-650            Output: 220/380V/230V/400V-Three Phase            Max. Operating PV Input Current: 36A +20A            Max Input Short-Circuit: 54A + 30A            No. of MPP Trackers: 2(2+1)            Peak Power: 2times of rated power, 10s            IP 65: 5years Warranty</p>	<p><b>3,500,000</b></p>
<p><b>8.</b></p>	<p><b>DEYE 20K (SUN-20K-SG05LP3-E)</b>            Battery Type: Lithium/Lead Acid: (40-60V)            Max. DC Charging Current(A) :350A            Maximum DC Discharging Current(A): 350A            Charging Strategy for Li-ion Battery (Self Adaption to BMS)            Max. PV Access Power: 40,000W            Max. PV Input Power: 32,000W            Max. PV. Input Voltage :800V            Start-up Voltage : 160V ,MPPT Voltage Range (V) 160-650            Output: 220/380V/230V/400V-Three Phase            Max. Operating PV Input Current: 36A +20A            Max Input Short-Circuit: 54A + 30A            No. of MPP Trackers: 2(2+1)            Peak Power: 2times of rated power, 10s            IP 65: 5years Warranty</p>	<p><b>4,350,000</b></p>
<p><b>9.</b></p>	<p><b>Deye 30kW (SUN-30K-SG01HP3-EU)</b>            Battery Type: Lithium/Lead Acid: (160-800V)            Max. DC Charging Current(A) : 50A+50A            Maximum DC Discharging Current(A): 50+50A            Charging Strategy for Li-ion Battery (Self Adaption to BMS)            Max. PV Access Power: 60,000W , Max. PV Input Power: 48,000W            Max. PV. Input Voltage: 1000V , Start-up Voltage : 180V            MPPT Voltage Range (V) 150-850, Output: 220V/380V,230/400-Three Phase            Max. Operating PV Input Current: 36A +36A+36A            Max Input Short-Circuit: 55A + 55A+55A            Output: 220/380V, 230V/400V-Three Phase            No. of MPP Trackers: 3(2+2+2),Peak Power: 2times of rated power, 10s            100% unbalanced output, Communication: RE485/RS232/CAN            Monitor Module: GPRS/WIFI/Bluetooth/4G/LAN            Max. 10 pcs parallel for on-grid and off-grid operation;            IP 65: 5years Warranty</p>	<p><b>5,000,000</b></p>

**“Prices are subject to daily fluctuations in foreign exchange”**

<p><b>10.</b></p>	<p><b>DEYE 50K (SUN-50K-SG01HP3-EU)</b>            Battery Type: Lithium/Lead Acid: (160-800V)            Max. DC Charging Current(A) : 50A+50A            Maximum DC Discharging Current(A): 50+50A            Charging Strategy for Li-ion Battery (Self Adaption to BMS)            Max. PV Access Power: 100,000W,Max. PV Input Power: 80,000W            Max. PV. Input Voltage: 1000V, Start-up Voltage : 180V            MPPT Voltage Range (V) 150-850, Output: 220V/380V,230/400-Three Phase            Max. Operating PV Input Current: 36A +36A+36A+36A            Max Input Short-Circuit: 55A + 55A+55A+55A            Output: 220/380V, 230V/400V-Three Phase            No. of MPP Trackers: 4(2+2+2+2)            Peak Power: 2times of rated power, 10s            100% unbalanced output, Communication: RE485/RS232/CAN            Monitor Module: GPRS/WIFI/Bluetooth/4G/LAN            Max. 10 pcs parallel for on-grid and off-grid operation;            IP 65: 5years Warranty</p>	<p><b>6,750,000</b></p>
<p><b>11.</b></p>	<p><b>DEYE 80KW-(SG02HP3-E)</b>            Battery Type: Lithium/Lead Acid: (160-1000V)            Max. DC Charging Current(A) : 80A+80A            Maximum DC Discharging Current(A): 80+80A            Charging Strategy for Li-ion Battery (Self Adaption to BMS)            Max. PV Access Power: 160,000W            Max. PV Input Power: 128,000W            Max. PV. Input Voltage: 1000V            Start-up Voltage : 180V            MPPT Voltage Range (V) 150-850            Output: 220V/380V,230/400-Three Phase            Max. Operating PV Input Current: 36A +36A+36A+36A+36A+36A            Max Input Short-Circuit: 54A+54A+54A+54A+54A+54A            No. of MPP Trackers: 6(2+2+2+2+2+2)            Peak Power: 1.5times of rated power, 10s            100% unbalanced output, Communication: RE485/RS232/CAN            Monitor Module: GPRS/WIFI/Bluetooth/4G/LAN            Max. 10 pcs parallel for on-grid and off-grid operation;            IP 65: 5years Warranty</p>	<p><b>9,900,000</b></p>

## THRILLHOUSE LIMITED

(20<sup>th</sup> June, 2026 ENERGY PRICE LIST )

(EXCEPTIONAL PRICE-QUALITY CORRELATION ON SOLAR ENERGY GADGETS)

**“Prices are subject to daily fluctuations in foreign exchange”**

### L. INVERTERS (TRANSFORMER BASED-PURE SINEWAVE)

S/N	SMARTENS INVERTERS (1 year warranty)	PRICE(N)
1	Smarten 1000va/12v	110,000.00
2.0	Smarten 1500va/12v	170,000.00
3.0	Smarten 1700va/24v	170,000.00
4.0	Smarten 2000va/24v	190,000.00
5.0	Smarten 2500va/24v	260,000.00
6.	Smarten 3200va/24v	280,000.00
7.	Smarten 3500VA/48V	330,000.00
8.	Smarten 5000VA/48V	690,000.00
9.	Smarten 7.5KVA/96V	750,000.00
10.	Smarten 10KVA/120V	950.000.00

### M. LG INVERTER AIR CONDITIONERS

S/N	LG WALL MOUNTED DUAL INVERTER AC 10year Warranty on Compressor, 1year Warranty	PRICE(N)
1.	1.0 HP LG Dual Inverter AC SPL 1.0HP GENCOOL -B LVS, HVS, R410 GAS , Copper Condenser, NB: Can be powered with a 700VA Generator	-----
2.	1.5 HP LG Dual Inverter AC SPL 1.5HP GENCOOL -B LVS, HVS, R410 GAS , Copper Condenser, NB: Can be powered with a 900VA Generator	515,000





**“Prices are subject to daily fluctuations in foreign exchange”**

**N. SOLAR PANELS**

	<b>MONO CRYSTALLINE SOLAR PANELS</b>	<b>PRICE (₱)</b>
	<b>JINKO/LONGI/TRINA SOLAR PANELS (N Type Half-Cell)10yrs Warranty, 30yrs+ Lifespan</b>	<b>Price</b>
1.	<b>440 Watts Jinko (Mono-Facial N-Type) (Model: JKM440N-54HL4R-V)</b>	<b>110,000</b>
2.	<b>575 Watts TRINA (Mono Facial) (Model: 575N-72HL4-BDV)</b>	<b>135,000</b>
3.	<b>580 Watts TRINA (Mono Facial) (Model: 580N-72HL4-BDV)</b>	<b>136,000</b>
4.	<b>590Watts Jinko (Bi-facial N-Type) (Model: 590N-72HL4-BD)</b>	<b>142,000</b>
5.	<b>620Watts Jinko (Bi-facial N-Type) (Model: 620N-66HL4-BD)</b>	<b>150,000</b>
6.	<b>625Watts Jinko (Bi-facial N-Type) (Model: 625N-66HL4-BD)</b>	<b>152,000</b>
7.	<b>625Watts Astro Energy (Bi-facial N-Type) (n-type TOPCon 5.0, ZBB Design)</b>	<b>155,000</b>
	<b>ITEL Panels 10years Warranty, 25years Lifespan</b>	<b>Price</b>
1.	<b>410W</b>	<b>105,000</b>




**“Prices are subject to daily fluctuations in foreign exchange”**

**O. PORTABLE POWER STATION (WITH BUILT IN LITHIUM BATTERY)**

S/N	Portable Power Station 12months warranty/24months warrantu	PRICE(₦)
<b>A.</b>	<b>XTRA POWER PORTABLE STATION</b>	
<b>1.</b>	<b>300WATTS SOLAR GENERATOR (XT300-SG 12V 25AH , 30AMPS CHARGER) + 110Watts Panels</b> 	<b>220,000.00</b>
<b>B.</b>	<b>ITEL ALL-IN-ONE POWER STATION</b>	
<b>1.</b>	<b>ITEL POWER GO (IESS-320T) 100,000mah(100Ah), 320Wh, A Grade LFP cell:3000cycles, Multi Charge Mode: PV/DC/Type-C. Max.Charge Power:100W. 8 Outputs Ports: Type-C*2/USB- A*4/DC5521*2. Output Power: 130Watts</b>	<b>105,000</b> 
<b>2.</b>	<b>IESS-05K10N (500watts AIO) ITEL 500Watts Portable Power Station 500W+1000WH+400W(MPPT) Inverter Capacity: 500Watts Battery Capacity: 1000Wh (3.2VDC,314Ah), 6000cycles, 8-10years performance lifespan</b>	<b>308,000</b> 
<b>3.</b>	<b>IESS-3K680N ALL-IN-ONE ITEL 3600Watts Power Station 3600W+8000WH+5KW(MPPT) Inverter Capacity: 3600Watts Battery Capacity: 8000Wh (25.6VDC,314Ah), 6000cycles, 8-10years performance lifespan MPPT Capacity: 5000Watts</b>	<b>Out of Stock</b> 

**“Prices are subject to daily fluctuations in foreign exchange”**

**P. SOLAR CHARGE CONTROLLER**

S/N	<b>PULSE WIDTH MODULATION (PWM) (1year Warranty)</b>		<b>PRICE (₹)</b>
1.	<b>12V-24V – 40AMPS (SRNE)-</b> Auto recognition, maximum PV input voltage @ 55v		<b>38,000.00</b>
2.	<b>12V-24V – 60AMPS (SRNE)</b> Auto recognition, maximum PV input voltage @ 55v		<b>65,000.00</b>
S/N	<b>MAXIMUM POWER POINT TRACKING(MPPT) (2 Years Warranty)</b>		<b>PRICE (₹)</b>
1.	<b>(SRNE NEW MODEL)</b> AUTO RECOGNITION, MPPT EFFICIENCY CAN REACH 99%. MAX INPUT VOLTAGE : <b>100V.</b> <b>HEAT SINK DESIGN</b> 	<b>20A</b>	<b>50,000.00</b>
		<b>30A</b>	<b>70,000.00</b>
		<b>40A</b>	<b>90,000.00</b>
		<b>60A</b>	<b>110,000.00</b>
2.	<b>12V/24V/36V/48V-60 AMPS</b> AUTO RECOGNITION, MPPT EFFICIENCY CAN REACH 99.9%. MAX INPUT VOLTAGE: <b>145V.</b> <b>FAN COOLING DESIGN</b> 		<b>130,000.00</b>
3.	<b>12V/24V/36V/48V-100 AMPS</b> AUTO RECOGNITION, MPPT EFFICIENCY CAN REACH 99.9%. MAX INPUT VOLTAGE: <b>250V.</b> <b>HEAT SINK DESIGN</b> 		-----
5.	<b>12V/24V/36V/48V-100 AMPS</b> AUTO RECOGNITION, MPPT Upto 6000Watts PV Capacity Dual MPPT Tracker MAX INPUT VOLTAGE: 500Vdc(3000Watts)B+500Vdc(3000Watts). 80 – 450V MPPT Voltage Range Startup voltage *120volts* <b>Upto 16pcs in parallel</b> 		-----

**“Prices are subject to daily fluctuations in foreign exchange”**

**Q. SOLAR FLOOD/SOLAR STREET LIGHTS**

<b>S/N</b>	<b>SOLAR FLOOD LIGHT</b>		<b>PRICE (₦)</b>
1.	<b>Bestcom (YL-2251 100W) Panel Size: 10watts Battery Capacity: 40Wh Installation height: 5-6m 2years Warranty</b>		<b>42,000</b>
2.	<b>BestCom (YL-2252 200W) Panel Size: 20watts Battery Capacity: 60Wh Installation height: 5-6m 2years Warranty</b>		<b>52,000</b>
3.	<b>BestCom 300Watts (YL-2253 300W) Panel Size: 30watts Battery Capacity: 80Wh Installation height: 5-6m 2years Warranty</b>		<b>65,000</b>
4.	<b>Wakatek WK JS-300Watts, 30watts GradeA Solar Panes LifeP04 Lithium Battery 150WH 5000 Lumens, 6-7hrs Charge time, 8-10yrs Lifespan 2years Warranty</b>		<b>75,000</b>
5	<b>Wakatek SOLAR STREET LIGHT 100W, 788Wh LFP battery, 120Watts Mono Panel 2years warranty.</b>		<b>215,000</b>
6	<b>Wakatek SOLAR STREET LIGHT 60W, 548.5Wh LFP battery, 90Watts Panel</b>		<b>155,000</b>
7	<b>Wakatek SOLAR STREET LIGHT 160W, 1058Wh LFP battery, 160Watts Mono Panel</b>		<b>295,000</b>






**“Prices are subject to daily fluctuations in foreign exchange”**

**R. SOLAR CAMERA,LOW WATTAGE ELECTRIC IRONS,FAN, EXTENSION**







<b>S/N</b>	<b>ITEMS</b>	<b>PRICE (₦)</b>
<b>1.</b>	<b>300Watts Sonik Low Energy IRON 5-Temperature Modes 100% Copper Cable Non-Sticj soleplate Power Light Indicator Suitable for Inverters from 1kW and Above</b>	 <b>15,000</b>
<b>2.</b>	<b>GREEN METERING PTZ SOLAR Camera 6MP 4G DUAL LENS SOLAR CAMERA 7.5WATTS PANEL, 10800MAH BATTERY, HORIZONTAL ROTATION: 0-355° VERTICAL ROTATION: 0-90° TWO-WAY AUDIO, PIR HUMAN DETECTION B/W Night Vision Or Colorful Night Vision Data Storage Options :Memory Card(supports upto 256GB), Cloud storage option(<b>With ESee Cloud</b>) IP Rating :ip66 (indoor and outdoor) Warranty (1 Year)</b>	 <b>75,000</b>
<b>3.</b>	<b>GREEN METERING PTZ SOLAR Camera 9MP 4G DUAL LENS SOLAR CAMERA 7.5WATTS PANEL, 10800MAH BATTERY, HORIZONTAL ROTATION: 0-355° VERTICAL ROTATION: 0-90° TWO-WAY AUDIO, PIR HUMAN DETECTION B/W Night Vision Or Colorful Night Vision Data Storage Options :Memory Card(supports upto 256GB), Cloud storage option(<b>With ESee Cloud</b>) IP Rating :ip66 (indoor and outdoor) Warranty (1 Year)</b>	 <b>85,000</b>
<b>4.</b>	<b>MAXI TABLE FAN40-17NB</b>	Maxi 16 Inches, Rated Power: 40W Oscillation Function.White <b>37,000</b>
<b>5.</b>	<b>ITEL Extension Socket</b>	ITEL2500Watts 4Pin EXTENSION OUTLET <b>5,000</b>

**“Prices are subject to daily fluctuations in foreign exchange”**

**S. SOLAR DC SUBMERSIBLE PUMP**

	<b>DC PUMPS AND SPECIFICATION: SODIBOHR (DC Brushless Copper Wire) Include pump and controller (ADS: Average daily supply)</b>	<b>PV Connection and Capacity</b>	<b>PRICE (₹)</b>
1.	200 Watts (3DS D3.5-26-24-200) Power : 200W Max. Flow(m <sup>3</sup> /h):3.5m <sup>3</sup> /h Max.Head:26m Outlet(in): 1.25” ADS: 20,000 Liters /day, Panel Voc < 50volts	 1unit of 485Wp	310,000
2.	300 Watts (3DS D3.5-38-24-300) Power:300W Max. Flow(m <sup>3</sup> /h):3.5m <sup>3</sup> /h Max.Head:38m Outlet(in): 1.25” ADS: 20,000 Liters /day, Panel Voc < 50volts	 1unit of 585Wp	-----
3.	<b>500 Watts (3DSD4-66-48-500)</b> Power: 500W; Max. Flow(m <sup>3</sup> /h): 4m <sup>3</sup> /h; Max.Head : 66m Outlet(in): 1.25” ADS: <b>25,000 Liters /day</b> , Panel Voc < 100volts	 <b>2units of 485Wp</b>	-----
4.	<b>750 Watts (3DSD4-100-72-750)</b> Power:750W; Max. Flow(m <sup>3</sup> /h):4m <sup>3</sup> /h Max.Head:100m Outlet(in): 1.25” ADS: <b>25,000 Liters /day</b> , Panel Voc < 150volts	 <b>3unit of 480Wp</b>	-----
5.	<b>750 Watts (3DSD6-74-110-750)</b> Power:750W; Max. Flow(m <sup>3</sup> /h): 6m <sup>3</sup> /h Max.Head:74m; Outlet(in):1.5” ADS: <b>36,000 Liters /day</b> Panel Voc < 200volts	 <b>3unit of 480Wp</b>	-----

**“Prices are subject to daily fluctuations in foreign exchange”**

<p><b>6.</b></p>	<p><b>750 Watts (3DSD7.5-53-110-750)</b> Power:750W; Max. Flow(m<sup>3</sup>/h): 7.5 m<sup>3</sup>/h Max.Head: 53m Outlet(in):1.5" <b>ADS:45,000 Liters /day, Panel Voc &lt; 200volts</b></p>	 <p><b>3unit of 480Wp</b></p>	<p>-----</p>
<p><b>7.</b></p>	<p><b>1100 Watts (3DSD4.5-126-150-1100)</b> Power: 1100W; Max. Flow(m<sup>3</sup>/h): 4.5 m<sup>3</sup>/h Max.Head: 126m Outlet(in): 1.25" <b>ADS: 36,000 Liters /day, Panel Voc &lt; 430volt</b></p>	 <p><b>3unit of 615Wp</b></p>	<p>-----</p>
<p><b>8.</b></p>	<p><b>1100Watts (3DSD6-101-150-1100)</b> Power: 1100W; Max. Flow(m<sup>3</sup>/h): 6.0 m<sup>3</sup>/h Max.Head: 101m Outlet(in): 1.5" <b>ADS:45,000 Liters /day, Panel Voc &lt; 430volt</b></p>	 <p><b>3unit of 615Wp</b></p>	<p>-----</p>
<p><b>9.</b></p>	<p><b>1100Watts (3DSD7.5-80-150-1100)</b> Power: 1100W Max. Flow(m<sup>3</sup>/h): 7.5 m<sup>3</sup>/h Max.Head: 80m Outlet(in): 1.5" <b>ADS: 50,000 Liters /day, Panel Voc &lt; 430volt</b></p>	 <p><b>3unit of 615Wp</b></p>	<p>-----</p>
<p><b>AC/ DC PUMPS AND SPECIFICATION: SODIBOHR (DC Brushless Copper Wire) Include pump and controller</b></p>		<p><b>PV Connection and Capacity</b></p>	<p><b>PRICE (₦)</b></p>
<p><b>10</b></p>	<p><b>750Watts (3DSD5.5-65-110-750A/D)</b> Power: 750W Max. Flow(m<sup>3</sup>/h): 5.5 m<sup>3</sup>/h Max.Head: 65m Outlet(in): 1.25" <b>EDS: 35,000 Liters /day, Panel Voc &lt; 200volt</b></p>	 <p><b>2units of 615 Watts</b></p>	<p>-----</p>
<p><b>11</b></p>	<p><b>1100Watts (3DSD5.5-90-110-1100A/D)</b> Voltage (DC) : 120-150V Power: 1100W Max. Flow(m<sup>3</sup>/h): 5.5 m<sup>3</sup>/h Max.Head: 90m Outlet(in): 1.25" <b>EDS: 35,000 Liters /day, Panel Voc &lt; 430volt</b></p>	 <p><b>3unis of 615Watts</b></p>	<p>-----</p>